

A·R·C·HITECTURAL

ROOF COATINGS

CLEANING SOLVENT

● **PRODUCT DATA SHEET**

● **DESCRIPTION**

100% hydrocarbon solvent. Flammable

● **RECOMMENDED USES**

Use this product to clean, tools, equipment and dissolve our DynaSHIELD products. A small amount added to ARC's DynaSHIELD TC 2000 will act as a drying agent.

● **HANDLING**

Use industrial chemical resistant gloves when using this product. Use a face mask and eye protection. Work with Cleaning Solvent outside where proper ventilation is available.

● **BENEFITS**

Cleans Tools
Dissolves Solvent-Based Products
Acts as a Drying Agent

● **TECHNICAL DATA**

AROMATIC CONTENT:	>99% ASTM D-1319
SPECIFIC GRAVITY:	15.6° C/15.6° C ASTM D-4052 value 0.874
COLOR:	Clear ASTM D-156 Saybolt +30
FIRE RATING:	Flammable ASTM D-56 °C value 46
VOC:	>500

**NEVER SMOKE WHEN USING CLEANING SOLVENT.
AVOID STATIC ELECTRICITY. GROUND EQUIPMENT.**

- *Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.*

DISTRIBUTED BY:

There is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. ARC assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY ROOF COATINGS, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.