

A·R·C·HITECTURAL

ROOF COATINGS

DynaSHIELD SEAM SEALER

• PRODUCT DATA SHEET

• DESCRIPTION

DynaSHIELD Seam Sealer is a proprietary blend of polymers. This is an oil-based, VOC compliant product. DynaSHIELD Seam Sealer flashes leaving a non-breathing, heat-reducing monolithic coating. It forms a water-repellent surface that easily cleans while resisting microorganisms.

• RECOMMENDED USES

This product may be applied over most roofing materials such as metal seams, BUR, Modified Asphalt Membranes, Single-Plies, butyl tape and polyester.

• APPLICATION

Surface to be treated must be clean and dry. If necessary, remove all dirt, grease, loose debris and residue before applying. DynaSHIELD Seam Sealer may be applied with a brush or extruded. Apply evenly at a surface temperature of 30° F or greater. When applying to thermoplastics, concrete, or other masonry surfaces, use a recommended primer.

• BENEFITS

- Easy To Apply
- Cleans Easily
- Long Shelf Life
- Freeze Resistant
- Year Round Usage
- Fast Curing
- Single Component

• TECHNICAL DATA

TENSILE:	1700 psi ASTM D-2370
ELONGATION:	500% ASTM D-2370
COLOR:	White
PERMEABILITY:	Non-breathing ASTM E-1653
SOLIDS:	Weight 58% +/- 2% ASTM D-1353
SOLIDS:	Volume 52% +/- 2% ASTM D-2697
WEIGHT:	10 lbs. per gallon +/- 2%
VISCOSITY:	Hand/Brush Grade
ABRASION:	Passed ASTM D-986
HARDNESS:	68 Shore A ASTM D-2240
STORAGE:	3 years unopened at 50° F - 80° F
DRY TIME:	1 hr. at 75° F and a thickness of 16 wet mils
FULL CURE:	12 - 72 hours depending on humidity, air movement, and temperature
CLEAN-UP:	Biodegradable Citrus Cleaning Products or ARC's Cleaning Solvent for oil-based products
ADHESION:	Pass ASTM D-3359
PIGMENT:	Titanium
FIRE RATING:	Class 'A' in Assembly

- Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.

DISTRIBUTED BY:

There is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. ARC assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY ROOF COATINGS, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.