

# A·R·C·HITECTURAL

## ROOF COATINGS

# HydroSHIELD STANDARD WHITE

### ● **PRODUCT DATA SHEET**

#### ● **DESCRIPTION**

HydroSHIELD Standard White is a blend of acrylic resins. It dries by evaporation to yield a non-yellowing, water-repellent surface. HydroSHIELD Standard White is UV stable, and has exceptional abrasion resistance. This product reduces surface temperatures and minimizes roof expansion and contraction.

#### ● **RECOMMENDED USES**

HydroSHIELD Standard White can be applied to surfaces such as metal, masonry, and wood after following preparation procedures.

#### ● **APPLICATION**

Surface to be treated must be clean. If necessary, remove all dust, grease and loose debris before applying this product. Apply with a brush, roller, or sprayer at a rate of 1.00 gallon per 100 square feet per pass, with a maximum of 3 gallons per 100 square feet total.

#### ● **BENEFITS**

Mildew Resistant	Non-Toxic
Flexible	Easy Clean Up
Non- Yellowing	Abrasion Resistant
Energy Saving	Prevents Rust
Waterproof	

#### ● **TECHNICAL DATA**

EMITTANCE:	.91 ASTM C-1371
REFLECTANCE:	.79% ASTM C-1549
FLEXIBILITY:	Passed 180° Mandrel Bend Test ASTM D-822
HAIL RESISTANCE:	Passed with no fracture of the membrane
WEATHERABILITY:	Passed 4000 hours ASTM G-53
FIRE RESISTANCE:	Class "A" ASTM E-108
FUNGAL RESISTANCE:	Passed ASTM D-3273-73T
ELONGATION:	200-250% ASTM D-2370
CLEAN UP:	Biodegradable Citrus Cleaning Products and/or soap and water
PERMEABILITY:	4.0 perms @ 20 mils ASTM E-1653
SOLIDS:	weight 55% +/- 2% ASTM D-1644
SOLIDS:	volume 42% +/- 2% ASTM D-2697

**CAUTION: High Humidity requires a longer time for water-based coatings to form a film that is rain resistant.**

- Avoid breathing fumes and prolonged contact with skin. Do not ingest. Keep containers covered when not in use. When using, provide proper ventilation. Dispose of product and container in accordance with local disposal codes.

#### **DISTRIBUTED BY:**

There is no warranty given, expressed or implied, through the values or statements made here, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by our in house and independent third party labs in order to obtain approval and/or classification. Acceptance, purchase and selection of these products are the sole responsibility of the buyer, buyer's agent, or the buyer's customer. ARC assumes no responsibility for coverage, performance, or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER GUARANTY OR WARRANTY OF ANY KIND IS MADE BY ROOF COATINGS, INC. OR ITS SUBSIDIARIES, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.